

AMENDMENTS TO THE CLAIMS

1-3. (Canceled):

4. (Previously Presented): A method of manufacturing a wheel bearing unit set forth in claim 10, wherein the processing comprises processing the side surface of the rotary flange into predetermined shape and dimension while rotating the rotary ring around the stationary ring in the state that the stationary ring, the rotary ring, and the plurality of rolling elements are assembled together.

5. (Previously Presented): A method of manufacturing a wheel bearing unit set forth in claim 10, wherein the processing comprises processing the braking friction surface into predetermined shape and dimension while rotating the rotary ring that couples/supports the braking rotating body around the stationary ring in a state that the stationary ring, the rotary ring, and the plurality of rolling elements are assembled together.

6. (Previously Presented) A method of manufacturing a wheel bearing unit set forth in claim 10, wherein the stationary ring is an outer ring that has an outer ring raceway as the stationary raceway on an inner peripheral surface as the stationary peripheral surface, and the rotary ring is a rotating member that is arranged on an inner diameter side of the outer ring and has an inner ring raceway as the rotary raceway on an outer peripheral surface as the rotary peripheral surface, and

wherein the processing comprises processing the side surface of the rotary flange provided to an outer peripheral surface of the rotating member into predetermined shape and dimension while rotating the rotating member around the outer ring in the state that the outer ring, the rotating member, and the plurality of rolling elements are assembled together.

7. (Canceled)

8. (Previously Presented): A method of manufacturing a wheel bearing unit set forth in claim 10, wherein the stationary ring is an outer ring that has an outer ring raceway as the stationary raceway on an inner peripheral surface as the stationary peripheral surface, and the rotary ring is a rotating member that is arranged on an inner diameter side of the outer ring and has an inner ring raceway as the rotary raceway on an outer peripheral surface as the rotary peripheral surface, and

wherein the processing comprises processing the braking friction surface of the braking rotating body into predetermined shape and dimension while rotating the rotating member around the outer ring in the state that the outer ring, the rotating member, and the plurality of rolling elements are assembled together.

9. (Canceled)

10. (Currently Amended) A method of processing a wheel bearing unit that includes a stationary ring that has a stationary raceway on a stationary peripheral surface and is not rotated in operation, a rotary ring that has a rotary raceway on a rotary peripheral surface and is rotated in operation, a plurality of rolling elements provided between the stationary raceway and the rotary raceway, an encoder fixed to a part of the rotary ring and at least a part of the encoder is made of a permanent magnet, a cover fixed on an opening portion of an axially inner end of the stationary ring and having an insertion hole for inserting a part of a holder of a sensor in operation, and a rotary flange provided to an outer peripheral surface of the rotary ring, wherein said rotary flange couples/supports a braking rotating body on a side surface of the rotary flange

at least in operation, the braking rotating body having a braking friction surface against which a friction material is pushed in a braking operation, comprising:

~~fixing an encoder to a part of the rotary ring, wherein at least a part of the encoder is made of a permanent magnet;~~

processing a portion of the wheel bearing unit or the braking rotating body into predetermined shape and dimension in a state that the stationary ring, the rotary ring, and the plurality of rolling elements are assembled together, wherein prior to the processing a space in which the encoder is provided is isolated from an outside by fitting a stop plug to the insertion hole of the cover ~~or a cover to a part of the stationary ring or the rotary ring directly or via another member~~, and

removing the stop plug from the cover ~~or the cover from the stationary ring or the rotary ring~~ after the portion of the wheel bearing unit is processed into predetermined shape and dimension but before the wheel bearing unit is fitted to a suspension system.